

Использование и доступ к командной строке ядра

Доступ к командной строке ядра сервера осуществляется через SSH на порту 2001. Для открытия можно использовать как Linux-SSH клиент командной строки так и любой другой, например Putty.

```
ssh -p 2001 localhost
username: admin
password: admin
```

Имя пользователя и пароль необходимо будет поменять на безопасные при вводе в эксплуатацию. Имя пользователя может быть изменено в файле настроек database.yml, пароль - при помощи команды passwd.

Кроме интерактивного доступа, поддерживается и доступ с [авторизацией по публичному ключу](#).

Наберите help в командной строке для получения справочной информации.

```
login as: admin
SSH server: Password authentication
Using keyboard-interactive authentication.
Password:
% help
Try one of these commands with the -h or --help switch:

NAME      DESCRIPTION
add        Add properties
call       Call commands
reload     Use to reload anything from server
stop       Stop command
passwd     change password
grep       search file(s) for lines that match a pattern
save       Save commands
show       Use to retrieve info from server
start      Start command
update     Update property
remove     Remove property
help       provides basic help
repl       list the repl or change the current repl
```

Для вывода подробной информации о команде можно воспользоваться ключом -h.

```
% update user -h
usage: update [-h | --help] user [-a | --active] <username>

    [-h | --help]    this help
    [-a | --active]  set active flag
```