The list of methods and their parameters

The complete list of methods and parameters

Grey denotes parameters described above or below in the table.

Depending on the direction and destination of the call, different subsets of parameters for the same invocation can be used. For example, in case of the invocation of ConnectionStatusEvent, sipLogin, sipPassword, and othe corresponding parameters are passed. In case of an error, the same event ConnectionStatusEvent will have only two parameters: status and info when sending to a client, and status, info, nodeId, sessionId, appKey when sending to the Web-server.

connect	**Establishes connection with the WCS Server**
urlServer	This parameter is used by WCS JavaScript API to connect to the server.
appKey	This parameter passes the REST - URL for the given application to WCS. To view and add applications use the command line interface (CLI).
sipRegisterRequired	If this parameter is true, registration on the SIP server is performed by invoking SIP REGISTER. If the parameter is false, registration on the SIP server is not performed. In this case, a web page cannot accept incoming SIP calls, but still can make outgoing calls if the SIP server allows outgoing calls without SIP registration.
sipLogin	SIP login of a user
sipAuthenticationName	SIP name of a user used for SIP authentication. Can be different from sipLogin.
sipPassword	SIP password. Used for SIP authentication.
sipVisibleName	SIP user name displayed to other users receiving an incoming call from this user.
sipDomain	SIP domain. FQDN or IP address.
sipOutboundProxy	SIP proxy server. FQDN or IP address. Can be different from sipDomain.
sipPort	SIP port the SIP server uses to handle SIP traffic.
sipContactParams	A string of custom parameters added to the SIP Connect header of the REGISTER query.
status	
mediaProviders	Array of available types of media on WCS JavaScript API: ['WebRTC','Flash'].
restClientConfig	A JSON-object describing web-server interaction control configuration. If the object isn't passed, the default values are used. See also:RestClientConfig.
width	Maximal video width, in pixels
height	Maximal video height, in pixels
ConnectionStatusEvent	**Connection status change**

sipRegisterRequired	
sipLogin	
sipPassword	
sipVisibleName	
sipDomain	
sipOutboundProxy	
sipPort	
sipContactParams	
status	WCS Server connection status:PENDING,ESTABLISHED,FAILED,DISCONNECTED.
info	Additional information can be added to this field. For example, if status==FAILED, the info contains the description of the reason.
authToken	A key being used in WCS JavaScript API for connection of Flash implementation to WCS server using RTMFP protocol.
mediaProviders	
nodeId	
sessionId	
appKey	
RegistrationStatusEvent	**SIP registration status change**
status	Registration statuses:REGISTERED,UNREGISTERED,FAILED.
info	
sipMessageRaw	Original SIP-message with headers. SIP Response to the REGISTER Request.
nodeId	
sessionId	
appKey	
call	**Outgoing call**
callId	Unique id of the call.
callee	A callee in the SIP URI format, tel URI or a telephone number.

caller	A caller in the SIP URI format.
visibleName	A label displayed to the callee.
hasVideo	If true, this is a video call.
inviteParameters	Parameters added to the SIP INVITE Request URI.
isMsrp	If true, this is not a voice call, but establishing of MSRP-connection to transmit data.
status	
incoming	If true, it is an incoming call from SIP side.
mediaProvider	Media technology used on WCS JavaScript API, possible values: "WebRTC", "Flash".
sdp	SDP, created on WCS JavaScript API side, will be placed when mediaProvider is WebRTC
OnCallEvent	**Incoming call**
callId	`
callee	
caller	
visibleName	
hasVideo	
inviteParameters	
sipMessageRaw	SIP INVITE message the incoming call even is based upon.
incoming	
status	
mediaProvider	
sdp	
nodeId	
sessionId	
appKey	
CallStatusEvent	**Call status change**
callId	

incoming	If true, the call is incoming
status	Call statuses:TRYING,RING,SESSION_PROGRESS,BUSY,ESTABLISHED,HOLD,FINISH,FAILED
info	
sipMessageRaw	Original message corresponding to the message being sent. For example, in case ofTRYING, this would be SIP 100 TRYING Response, in case ofESTABLISHEDthis would SIP 200 OK Response, and in case ofHOLDthis would be SIP 200 OK Response to re-INVITE, and so on.
sipStatus	Response status received from SIP side
caller	
callee	
hasVideo	
visibleName	
mediaProvider	
nodeId	
sessionId	
appKey	
answer	**Answer incoming call**
callId	
incoming	
sipStatus	
caller	
callee	
hasVideo	
visibleName	
mediaProvider	
sdp	
status	
nodeId	
sessionId	
appKey	
hangup	**Hangs up the call**
callId	

hasVideo	
nodeId	
sessionId	
appKey	
hold	**Puts the call on hold**
callId	
hasVideo	
nodeId	
sessionId	
appKey	
unhold	**Unhold the call**
callId	
hasVideo	
nodeId	
sessionId	
appKey	
transfer	**Transfer the call**
callId	
target	The number or the SIP URI of the subscriber the call is transferred to.
nodeId	
sessionId	
appKey	
TransferStatusEvent	**Call transfer status change**
callId	
incoming	If true, the transfer was initiated by the other side.
status	Call transfer statuses: ACCEPTED, TRYING, COMPLETED, FAILED. If the status is not recognized, then status received from SIP side will be passed.
info	
sipMessageRaw	

hasVideo	
nodeId	
sessionId	
appKey	
sendDTMF	**Sends DTMF signal**
callId	
dtmf	A symbol to pass in DTMF as text: 1-16, *, #.
type	The type of the DTMF signal:INFO,INFO_RELAY,RFC2833.
nodeId	
sessionId	
appKey	
sendMessage	**Sends a message**
id	The unique id of the message.
from	The number of the SIP URI of the sender.
to	The number, the login or the SIP URI of the recipient.
body	The text of the message.
contentType	text/plain- the message is sent as SIP MESSAGE with the 'Content-Type : text/plain' header and with text in the body of the message. message/cpim- the message is sent as SIP MESSAGE with the 'Content-Type:message/cpim' header and a text/plain message in the body of the CPIM-message. multipart/mixed- the message is sent as SIP MESSAGE with the 'Content-Type:multipart/mixed' header and CPIM messages in the body, each one containing one text/plain message.
isImdnRequired	If the flag is set to true, for message/cpim and multipart/mixed message types, the information asking for a delivery notification via IMDN will be added to the body of the CPIM message.
recipients	The list of recipients separated by commas. SIP URI, tel URI or SIP logins of recipients must be specified and separated by commas. The field is used only if ContentType is set to multipart/mixed. This field works correctly only when the SIP-server supports sending messages to multiple subscribers based on multipart/mixed. WCS sends a multipart/mixed message with multiple recipients to the SIP-server. If your SIP-server doesn't support such sending, leave this field blank and try sending several individual messages.
nodeId	
sessionId	
appKey	
OnMessageEvent	**Incoming message**
id	
from	

to	
body	
contentType	
isImdnRequired	If the incoming message has this flag, an IMDN delivery notification will be sent.
sipMessageRaw	A SIP MESSAGE message that corresponds to the OnMessageEvent event of the incoming message.
status	
nodeId	
sessionId	
appKey	
MessageStatusEvent	**Message status change**
id	
from	
to	
contentType	
isImdnRequired	
body	
status	Message statuses:RECEIVED,ACCEPTED,FAILED,IMDN_DELIVERED,IMDN_FAILED, IMDN_NOTIFICATION_SENT
info	
sipMessageRaw	SIP message corresponding to the status: ACCEPTED- SIP 200 OK Response to SIP MESSAGE Request. FAILED- SIP 4xx Response from the SIP-server. DELIVERED- received a SIP MESSAGE delivery notification with the status 'Delivered'. DELIVERY_FAILED- received a delivery notification with the status 'Delivery Failed'.
nodeId	
sessionId	

appKey	
sendIMDN	**Sends IMDN delivery notification**
messageId	
nodeId	
sessionId	
appKey	
subscribe	**SIP subscribe - subscribe to notification of the SIP-server.RFC3265.**
event	Event type:reg
expires	Time interval in seconds. During this interval the WCS-server performs re-SUBSCRIBE.
terminate	
nodeId	
sessionId	
appKey	
SubscriptionStatusEvent	**SIP-subscription status change**
event	
expires	
terminate	If true, the subscription should be deactivated
requestBody	XML received from SIP side
status	Subscription statuses:Active,Terminated
info	
sipMessageRaw	SIP message changing the status of the subscription: Active- SIP 200 OK Response on SUBSCRIBE Request. Terminated- SIP 200 OK Response on SUBSCRIBE Request with expires:0. Terminated- SIP NOTIFY Request with the 'terminated' status in the body of the NOTIFY message.
nodeId	
sessionId	

appKey	
sendXcapRequest	**Send an XCAP request**
url	URL for the XCAP request
nodeId	
sessionId	
appKey	
XcapStatusEvent	**Receiving XCAP response**
url	
xcapResponse	The body of the XCAP response
publishStream	**Publishing the stream to the server**
name	The name of the published stream. Must be unique. If a stream with such name already published, the publishing of the stream is prohibited.
mediaSessionId	Identifier of media session
published	If true, the stream is being published
hasVideo	If true, the stream has video
status	
sdp	SDP received from client
nodeId	
sessionId	
appKey	
record	If true, the published stream is being recorded
unPublishStream	**Unpublishing the stream**
name	
mediaSessionId	
published	
hasVideo	
status	
sdp	

nodeId	
sessionId	
appKey	
record	
playStream	**Play the stream**
name	The name of the played stream.
mediaSession	
published	
hasVideo	
status	
sdp	
nodeId	
sessionId	
appKey	
playHLS	**Play the stream via HLS**
name	
mediaSessionId	
mediaProvider	
nodeId	
sessionId	
appKey	
token	Client authentication token
playRTSP	**Play the stream via RTSP**
name	
mediaSessionId	
mediaProvider	
nodeId	

sessionId	
appKey	
rtspUrl	RTSP stream URL
User-Agent	Client User-Agent
stopStream	**Stop playback of the stream**
name	
mediaSessionId	
published	
hasVideo	
status	
sdp	
nodeId	
sessionId	
appKey	
StreamStatusEvent	**Stream status change**
name	
status	Stream status:PUBLISHING,UNPUBLISHED,PLAYING,STOPPED
mediaSessionId	
published	
hasVideo	
sdp	
info	
nodeId	
sessionId	
appKey	
record	

StreamKeepAliveEvent	**Stream keep-alive REST request**
nodeId	
appKey	
sessionId	
mediaSessionId	
name	
published	
hasVideo	
status	Stream status:PLAYING, PUBLISHING
info	
mediaProvider	Media technology used on WCS JavaScript API, possible values: "WebRTC", "Flash"
record	
sendData	**Sends data**
operationId	Unique id of the data to send.
payload	JSON object containing data.
nodeId	
sessionId	
appKey	
OnDataEvent	**Receiving of input data**
operationId	
payload	
nodeId	
sessionId	
appKey	
DataStatusEvent	**Sent data status change**

operationId	
status	ACCEPTED,FAILED
info	
nodeId	
sessionId	
appKey	
ErrorEvent	**Unclassified error**
info	Additional information about the error.
sendBugReport	**Sends an error report to save on the server**
text	Brief custom description of the error.
type	If the type isno_media,the server enables traffic dump before creating a bug report to make sure the traffic goes properly for that user. Sending bug reports of this type can help diagnose problems with sound going one side only.
nodeId	
sessionId	
appKey	
BugReportStatusEvent	**Error report sending confirmation with the name of the saved file as the output**
filename	The name of the file on the server where the bug report was saved.
nodeId	
sessionId	
appKey	
ContextParameters	**Context parameters. Used for all calls from WCS to the Web-server.**
nodeId	Unique id of the WCS server instance.
sessionId	Unique id of the client connect in that instance.
appKey	Application id on the WCS server the user has established connection with.