

Stack trace logging

When an error occurs, an exception stack trace is logged, for example

```
09:55:51,203 WARN  olNegotiationHandler -nioEventLoopGroup-3-2 [id: 0x3cee8c80, L:0.0.0.0/0.0.0.0:8445 ! R:  
/192.168.1.179:31032] TLS handshake failed:  
javax.net.ssl.SSLHandshakeException: error:100000f7:SSL routines:OPENSSL_internal:WRONG_VERSION_NUMBER  
    at io.netty.handler.ssl.ReferenceCountedOpenSslEngine.sslReadErrorResult(ReferenceCountedOpenSslEngine.  
java:1334)  
    at io.netty.handler.ssl.ReferenceCountedOpenSslEngine.unwrap(ReferenceCountedOpenSslEngine.java:1295)  
    at io.netty.handler.ssl.ReferenceCountedOpenSslEngine.unwrap(ReferenceCountedOpenSslEngine.java:1371)  
    at io.netty.handler.ssl.ReferenceCountedOpenSslEngine.unwrap(ReferenceCountedOpenSslEngine.java:1414)  
    at io.netty.handler.ssl.SslHandler$SslEngineType$1.unwrap(SslHandler.java:224)  
    at io.netty.handler.ssl.SslHandler.unwrap(SslHandler.java:1338)  
    at io.netty.handler.ssl.SslHandler.decodeNonJdkCompatible(SslHandler.java:1245)  
    at io.netty.handler.ssl.SslHandler.decode(SslHandler.java:1282)  
    at io.netty.handler.codec.ByteToMessageDecoder.decodeRemovalReentryProtection(ByteToMessageDecoder.java:  
507)  
    at io.netty.handler.codec.ByteToMessageDecoder.callDecode(ByteToMessageDecoder.java:446)  
    at io.netty.handler.codec.ByteToMessageDecoder.channelRead(ByteToMessageDecoder.java:276)  
    at io.netty.channel.AbstractChannelHandlerContext.invokeChannelRead(AbstractChannelHandlerContext.java:  
379)  
    at io.netty.channel.AbstractChannelHandlerContext.invokeChannelRead(AbstractChannelHandlerContext.java:  
365)  
    at io.netty.channel.AbstractChannelHandlerContext.fireChannelRead(AbstractChannelHandlerContext.java:  
357)  
    at io.netty.channel.DefaultChannelPipeline$HeadContext.channelRead(DefaultChannelPipeline.java:1410)  
    at io.netty.channel.AbstractChannelHandlerContext.invokeChannelRead(AbstractChannelHandlerContext.java:  
379)  
    at io.netty.channel.AbstractChannelHandlerContext.invokeChannelRead(AbstractChannelHandlerContext.java:  
365)  
    at io.netty.channel.DefaultChannelPipeline.fireChannelRead(DefaultChannelPipeline.java:919)  
    at io.netty.channel.nio.AbstractNioByteChannel$NioByteUnsafe.read(AbstractNioByteChannel.java:166)  
    at io.netty.channel.nio.NioEventLoop.processSelectedKey(NioEventLoop.java:719)  
    at io.netty.channel.nio.NioEventLoop.processSelectedKeysOptimized(NioEventLoop.java:655)  
    at io.netty.channel.nio.NioEventLoop.processSelectedKeys(NioEventLoop.java:581)  
    at io.netty.channel.nio.NioEventLoop.run(NioEventLoop.java:493)  
    at io.netty.util.concurrent.SingleThreadEventExecutor$4.run(SingleThreadEventExecutor.java:989)  
    at io.netty.util.internal.ThreadExecutorMap$2.run(ThreadExecutorMap.java:74)  
    at io.netty.util.concurrent.FastThreadLocalRunnable.run(FastThreadLocalRunnable.java:30)  
    at java.lang.Thread.run(Thread.java:748)
```

In this example, client sent a wrong data packet while establishing a secure connection to the HLS playback port.

Stack trace contains a useful information to debug the error, but Java machine may hide it for certain exceptions such as `NullPointerException`. To enable stack trace logging, add the following parameter to [wcs_core.properties](#) file

```
-XX:-OmitStackTraceInFastThrow
```