

# Main commands

WCS is managed using the following main commands:

## 1. Operating system command line

Command	Description	
<b>**Main commands to start and stop the server**</b>		
<code>`service webcallserver start`</code>	Start the server	
<code>`service webcallserver stop`</code>	Stop the server	
<code>`service webcallserver restart`</code>	Restart the server	
<b>**Additional commands**</b>		
<code>`/usr/local/Flashphoner WebCallServer/bin/webcallserver start`</code>	Start the server	
<code>`/usr/local/Flashphoner WebCallServer/bin/webcallserver start standalone`</code>	Start the server in the std out output mode for debugging purposes	
<code>`/usr/local/Flashphoner WebCallServer/bin/webcallserver stop`</code>	Stop the server	

## 2. WCS core command line interface

Command	Description
<code>show server-status</code>	Show the current status of the server: the number of active connections, ports, streams, CPU time consumed, RAM and disk usage, overall amount of sent and received data as well as elapsed time of the server.
<code>show users</code>	Show the list of users

Command	Description
<code>show node-settings</code>	Show current server settings or export them to a CSV file
<code>add user</code>	Add a new user
<code>update user</code>	Change user data
<code>remove user</code>	Remove a user
<code>show apps</code>	Show all available applications
<code>add app</code>	Add a new application
<code>update app</code>	Change applications settings
<code>remove app</code>	Remove an application

You can read a through description of the WCS core command line interface in [this section](#).